



INVESTOR IN PEOPLE



PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 13 JUL 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Stephen Hordley

Dated

1 July 2004

BEST AVAILABLE COPY

Patents Form 1/77 SW

Patents Act 1977
(Rule 16)

THE PATENT OFFICE

23 JUN 2003

RECEIVED BY FAX



1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form.)

23 JUN 2003

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ**1. Your reference**

AA 1659 QB

2. Patent application number
(The Patent Office will fill in)

0314463.1

23JUN03 E816777-1 001091
P01/7700 0.00-0314463.1**3. Full name, address and postcode of the or of each applicant (underline all surnames)**JOHNSON MATTHEY PUBLIC LIMITED COMPANY
2-4 COCKSPUR STREET
TRAFALGAR SQUARE
LONDON SW1 5BQ

Patents ADP number (if you know it)

536268009

If the applicant is a corporate body, give the country/state of its incorporation

GB.

*

4. Title of the inventionMETHOD OF CALIBRATING REDUCTANT
INJECTION IN A SCR SYSTEM**5. Name of your agent (if you have one)**

ANDREW DOMINIC NUNN

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)JOHNSON MATTHEY TECHNOLOGY CENTRE
BLOUNT'S COURT
SONNING COMMON
READING RG4 9NH

Patents ADP number (if you know it)

3991411001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number.

Country

Priority application number
(if you know it)Date of filing
(day / month / year)**7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application**

Number of earlier application

Date of filing
(day / month / year)**8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:**

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (2).

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description

Claim(s)

Abstract

Drawing(s)

8 / 85
7 /

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

1 CONTINUATION OF Box 3.

11.

I/We request the grant of a patent on the basis of this application.

Signature

Andrew Nunn

Date 25/6/03.

12. Name and daytime telephone number of person to contact in the United Kingdom

FRANCES STRANGE 0118 924 2125

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

"METHOD OF CALIBRATING REDUCTANT INJECTION IN A SCR SYSTEM"

Continuation of Box 3.

EMINOX LIMITED
NORTH WARREN ROAD
GAINSBOROUGH
LINCOLNSHIRE
DN21 2GU

4019105001

DUPLICATE

METHOD OF CALIBRATING REDUCTANT
INJECTION IN A SCR SYSTEM

5 The present invention relates to a method and apparatus for mapping injection of a reductant, such as a NO_x specific reactant, onto NO_x in exhaust gas from a lean-burn internal combustion engine. More particularly, it relates to such a method and apparatus wherein the engine comprises an exhaust system comprising a selective catalytic reduction (SCR) catalyst for reducing NO_x to N_2 with the reductant, thereby to meet a desired emission standard for NO_x .

10 By " NO_x " herein, we mean "nitrogen oxides" including "nitrogen monoxide (NO)" and "nitrogen dioxide (NO_2)". Whilst we refer herein to " NO_x sensors", by this we mean also sensors that measure total NO_x , sensors that can selectively detect the amount of NO in the NO_x present and also sensors that can selectively detect the amount of NO_2 in the NO_x present.

15 It has been suggested to use neural networks (or fuzzy logic) in process design and process modelling in exhaust systems for internal combustion engines (see e.g. SAE 2000-01-0212 "Three-way Catalytic Converter Modelling: Neural Networks and Genetic Algorithm for the Reaction Kinetics Submodel", L. Glielmo et al.) In computing terms, neural networks have a number of advantages over theoretical modelling or modelling based on experimentally
20 measured input-output data to build an empirical model. They can learn from experience; generalise from examples; and abstract essential information from "noisy" data. However, they can only provide good results for certain types of problem, and then only when a great deal of care is taken over neural network design and input data pre-processing data.

25 Reductant injection into exhaust systems of lean-burn internal combustion engines for the purpose of reducing NO_x to N_2 over a suitable catalyst is known. Such an approach is generally termed "selective catalytic reduction" or SCR. Where the reductant is a hydrocarbon, such as the fuel used to power the engine, the technology is generally called hydrocarbon SCR, or lean NO_x catalysis and the catalysts are called SCR catalysts, or more specifically, lean NO_x catalysts or
30 denox catalysts. Typical catalysts are copper exchanged zeolite e.g. ZSM5 or platinum on alumina. NO_x in the exhaust gas competes with other oxidising agents such as oxygen (O_2) for the hydrocarbon, and NO_x conversion in a drive cycle is of the order of about 40%. Accordingly, this form of SCR is sometimes referred to as non-selective SCR or NSCR.

An alternative form of SCR uses NO_x specific reactants as reductants and reduction is more selective than lean NO_x catalysis. Typical catalysts comprise platinum, supported vanadium (V₂O₅) e.g. on titania (TiO₂) or zeolites e.g. mordenite. For reasons that will become obvious, this form of SCR is often referred to as ammonia (NH₃)-SCR.

5

By "NO_x specific reactant" herein, we mean a reducing agent that, in most conditions, preferentially reduces NO_x over other components of a gaseous mixture. Examples of NO_x-specific reactants include nitrogenous compounds such as nitrogen hydrides, e.g. ammonia (NH₃) or hydrazine, or an NH₃ precursor.

10

By "NH₃ precursor" we mean one or more compounds from which NH₃ can be derived, e.g. by hydrolysis. These include urea (CO(NH₂)₂) as an aqueous solution or as a solid or ammonium carbamate (NH₂COONH₄). If the urea is used as an aqueous solution, a eutectic mixture, e.g. a 32.5% NH₃ (aq), is preferred. Additives can be included in the aqueous solutions

15

to reduce the crystallisation temperature.

Urea hydrolyses at temperatures above 160°C according to equation (1) to liberate NH₃ itself. It also thermally decomposes at this temperature and above according to equations (2) and (3) resulting in reduction of NO_x.

20



25

The NH₃ can be in anhydrous form or as an aqueous solution, for example.

The application of NH₃ SCR technology to treat NO_x emissions from IC engines, particularly lean-burn IC engines, is well known. Several chemical reactions occur in the NH₃ SCR system, all of which represent desirable reactions which reduce NO_x to elemental nitrogen.

30

The dominant reaction mechanism is represented in equation (4).



Competing, non-selective reactions with oxygen can produce secondary emissions or may unproductively consume NH_3 . One such non-selective reaction is the complete oxidation of NH_3 , represented in equation (5).




Presently, urea is the preferred source of NH_3 for mobile applications because it is less toxic than NH_3 , it is easy to transport and handle, is inexpensive and commonly available.

10 Early methods of using urea as a source of NH_3 in exhaust systems involved injecting urea directly into the exhaust gas, optionally over an in-line hydrolysis catalyst (see EP-A-0487886 (incorporated herein by reference)). However, not all urea is hydrolysed in such arrangements, particularly at lower temperatures.

15 Incomplete hydrolysis of urea can lead to increased PM emissions on tests for meeting the relevant emission test cycle because partially hydrolysed urea solids or droplets will be trapped by the filter paper used in the legislative test for PM and counted as PM mass. Furthermore, the release of certain products of incomplete urea hydrolysis, such as cyanuric acid, is environmentally undesirable. Another method is to use a pre-injection hydrolysis reactor (see
20 US-A-5,968,464 (incorporated herein by reference)) held at a temperature above that at which urea hydrolyses.

It will be appreciated that at lower temperatures, below about $100\text{-}200^\circ\text{C}$, NH_3 can also react with NO_2 to produce explosive ammonium nitrate (NH_4NO_3) according to equation (6):



For the avoidance of doubt, in so far as the invention uses NH_3 -SCR, the present invention does not embrace reactions such as reaction (6) or the promotion of conditions which
30 bring them about. For example, the reaction can be avoided by ensuring that the temperature does not fall below about 200°C or by supplying into a gas stream less than the precise amount of NH_3 necessary for the stoichiometric reaction with NO_x (1 to 1 mole ratio). For cold start applications, measures to prevent water from contacting the catalyst can be adopted. These can include disposing a water trap, e.g. a zeolite, upstream of the catalyst to reduce the amount of

water vapour contacting the catalyst until it is heated sufficiently. A water trap can also be positioned downstream of the catalyst, to prevent atmospheric humid air from travelling up the exhaust pipe. An electric heater can also be employed to drive off moisture from the catalyst pre-cold start. Such arrangements are described in our EP 0747581, (incorporated herein by
5 reference).

One problem in adopting SCR technology is controlling the addition of the reductant: if too little reductant is added, NO_x conversion may be insufficient to meet emission standards. On the other hand, if too much reductant it may be exhausted to atmosphere - hydrocarbon is a
10 legislated pollutant and NH_3 is a biological poison and is detected as NO_x in tests for meeting such standards.

In order to avoid such problems, extensive bench testing and modelling is carried out to establish engine maps and look-up tables to match e.g. urea injection to engine-out NO_x .
15 However, such testing is time consuming and extremely expensive.

We have now devised a method of establishing such maps and look-up tables which overcomes problems associated with the prior art and is particularly applicable to the retrofit market. In retrofit applications, the invention is based on the idea of fitting NO_x sensors to the
20 exhaust system of the vehicle, preferably downstream of the SCR catalyst, to input measurements on NO_x detected in the system to a suitable processor means, e.g. the vehicle's electronic control unit (ECU). The ECU may be the engine control unit or separate therefrom but communicable with the engine control unit. The ECU is used to correlate NO_x values with at least one additional physical variable indicative of the condition of the engine. The vehicle is
25 then driven normally for a period of, say, a few weeks, during which time the processor processes and collects the correlated data. Finally, the NO_x sensors can be removed and the vehicle, now comprising a processor that actuates reductant injection in response to detected input from the at least one additional physical variable indicative of the condition of the engine, can be used normally.

30

Accordingly, the expense and time normally required to develop maps for reductant injection can be avoided. Furthermore, certain embodiments of the invention comprise empirical determination of the amount of reductant required to treat NO_x , the method is more likely to reduce NO_x emissions than data generated from models or bench testing. A further advantage

springs from the fact that, since NO_x sensors can be removed following mapping, the problems of NO_x sensor cost and durability is reduced or avoided. Moreover, it is known from e.g. EP 1054722 that NO_x conversion over certain SCR catalysts can be improved if the NO:NO₂ ratio is adjusted to a particular range of values. Accordingly, by positioning a NO_x sensor upstream of the SCR catalyst, it may also be possible to adjust NO:NO₂ ratio e.g. at selected temperatures for optimal NO_x conversion.

The methods of the invention can use established techniques such as neural network technology. Adequate safeguards such as "mop-up" oxidation catalysts to prevent excessive emission of hydrocarbon or NH₃ to atmosphere during collection of such generalisation data or testing of training algorithm can be provided as necessary.

Therefore, according to a first aspect, the invention provides a method of mapping reductant injection onto NO_x in exhaust gas in a vehicle comprising a lean-burn internal combustion engine and an exhaust system comprising a selective catalytic reduction (SCR) catalyst for reducing NO_x to N₂ with the reductant, thereby to meet a desired emission standard for NO_x, which method comprising measuring NO_x in the exhaust gas as the vehicle is driven and correlating a measured NO_x value with a value of at least one measurable parameter indicative of a condition of the engine.

The method of the present invention is particularly applicable to the retrofit market, e.g. so that vehicles can be meet certified standards to enter areas, such as parts of cities, wherein access is denied to vehicles not meeting proscribed emissions standards. Therefore, according to a second aspect, the invention provides a method of retrofitting a vehicle comprising a lean-burn internal combustion engine with a system for meeting a desired emission standard for NO_x, which system comprising means for injecting a reductant into exhaust gas and a selective catalytic reduction (SCR) catalyst for reducing NO_x to N₂ with the reductant, which method comprising fitting the existing exhaust system with at least one NO_x sensor for measuring NO_x in the exhaust gas as the vehicle is driven and correlating a measured NO_x value with a value of at least one measurable parameter indicative of a condition of the engine

In one embodiment according to the first or second aspect of the invention, the method comprises the step of using the correlated value to determine the amount of reductant required to

reduce the measured value of NO_x by a desired amount for the measured value of the at least one measurable parameter.

5 In its broadest aspect, the invention enables collection of correlated data and "off-line", e.g. using bench engine analysis, to arrive at amounts of reductant to be injected into the system to reduce NO_x by a desired amount. However, in a preferred embodiment, the determination of reductant amounts is performed "on-line" as the vehicle is driven providing empirically measurable "finessing" of reductant addition through measurement of NO_x and/or reductant e.g. downstream of the SCR catalyst to arrive at adjusted reductant amount values.

10

Therefore, in particular embodiments of the first and second aspect, the method comprises the step of injecting the amount of reductant so-determined as the vehicle is driven, measuring exhaust gas downstream of the SCR catalyst for the presence of reductant and/or NO_x and adjusting the so-determined amount of reductant to reduce NO_x emissions and/or prevent reductant slip as necessary. Such a "learned" response is an aspect of neural network or "fuzzy logic" technology.

15 In an embodiment according to either the first or second aspect of the invention, as appropriate, the or each correlation step, the or each step of determining the amount of reductant and/or the step of adjusting the so-determined amount of reductant to reduce NO_x emissions and/or prevent reductant slip is performed by a processor. Such processor can be part of an electronic control unit (ECU).

25 According to a further embodiment of the first and second aspects of the invention, the correlated values, the amounts of reductant determined and/or the adjusted reductant amounts are stored as look-up tables or maps, for example, in the ECU.

30 Ordinarily, modern vehicle ECU's for controlling engine function do not have the processor and/or storage capability necessary for applying the methods according to the first and second aspects of the invention. It is envisaged, therefore, that in the first or second aspect the vehicle ECU is removed and replaced for the period of mapping with an ECU with the necessary processor and/or storage capacity. Following the mapping procedure, the original ECU can be re-programmed with the appropriate look up tables or maps and algorithms or a fresh ECU so-programmed can be inserted. Of course, if the original ECU of the vehicle has the required

processor and/or storage capacity, no such ECU switching/re-programming is necessary. Alternatively, the capacity of the original ECU can be supplemented by additional processor/storage capacity for the period of the analysis.

5 In one particular aspect according to the first aspect of the invention, NO_x is detected using at least one NO_x sensor positioned either upstream and/or downstream of the SCR catalyst. However, since NO_x sensors are expensive and have limited durability, the first and second aspects of the invention can comprise the steps of removing the at least one NO_x sensor after the amount of reductant required to reduce the measured value of NO_x as indicated by the measured
10 value of the at least one measurable parameter has been determined or the determined value has been adjusted. Thereafter, it is possible to treat the NO_x by detecting the at least one measurable parameter indicative of a condition of the engine and injecting an amount of reductant appropriate to the value detected.

15 The at least one measurable parameter can be any parameter indicative of the condition of the engine. It is envisaged that one or more of the following may be used: exhaust gas temperature; mass flow of exhaust gas in the system; manifold vacuum; ignition timing; engine speed; throttle position (accelerator position); the lambda value of the exhaust gas; the quantity of fuel injected in the engine; the position of the exhaust gas recirculation (EGR) valve and
20 thereby the amount of EGR; boost pressure; and engine coolant temperature. Sensors for measuring all these parameters are known to the skilled person.

The reductant can be a hydrocarbon and the SCR catalyst can be a lean NO_x catalyst e.g. any of those mentioned above, or the reductant can be a NO_x specific reactant, such as a nitrogen
25 hydride, e.g. ammonia (NH_3) or hydrazine, or an NH_3 precursor and the SCR catalyst can be a platinum-based catalyst, a supported vanadium such as $\text{V}_2\text{O}_5/\text{TiO}_2$ or a zeolite, such as mordenite. The NH_3 precursor can be urea ($\text{CO}(\text{NH}_2)_2$) or ammonium carbamate ($\text{NH}_2\text{COONH}_4$), for example.

30 According to a third aspect, the invention comprises an apparatus for mapping reductant injection onto NO_x in exhaust gas in a vehicle comprising a lean-burn internal combustion engine and an exhaust system comprising a selective catalytic reduction (SCR) catalyst for reducing NO_x to N_2 with the reductant, thereby to meet a desired emission standard for NO_x , which apparatus comprising at least one NO_x sensor for measuring NO_x in the exhaust gas,

means for measuring at least one measurable parameter indicative of a condition of the engine and means for correlating a measured NO_x value with the value for the at least one measurable parameter.

5 The at least one NO_x sensor is preferably downstream of the SCR catalyst. Where the system also includes a reductant sensor, this also is preferably positioned downstream of the SCR catalyst. The system also can comprise a source of reductant, e.g. a hydrocarbon fuel such as diesel or a NO_x specific reactant as defined herein.

10 According to a fourth aspect, the invention provides a vehicle comprising an apparatus according to the invention. Such vehicle can be powered by any suitable fuel such as gasoline or preferably diesel. Alternative fuel such as liquid petroleum gas, natural gas and methanol may also be used.

15 Where the vehicle comprises a diesel engine, it can be a heavy-duty diesel engine or light duty diesel engine according to the relevant legislation.

CLAIMS:

1. A method of mapping reductant injection onto NO_x in exhaust gas in a vehicle comprising a lean-burn internal combustion engine and an exhaust system comprising a selective catalytic reduction (SCR) catalyst for reducing NO_x to N₂ with the reductant, thereby to meet a desired emission standard for NO_x, which method comprising measuring NO_x in the exhaust gas as the vehicle is driven and correlating a measured NO_x value with a value of at least one measurable parameter indicative of a condition of the engine.
2. A method according to claim 1, comprising the step of using the correlated value to determine the amount of reductant required to reduce the measured value of NO_x to/by a desired amount for the measured value of the at least one measurable parameter.
3. A method according to claim 2, comprising the step of injecting the amount of reductant so-determined as the vehicle is driven, measuring exhaust gas downstream of the SCR catalyst for the presence of reductant and/or NO_x and adjusting the so-determined amount of reductant to reduce NO_x emissions and/or prevent reductant slip as necessary.
4. A method of retrofitting a vehicle comprising a lean-burn internal combustion engine with a system for meeting a desired emission standard for NO_x, which system comprising means for injecting a reductant into exhaust gas and a selective catalytic reduction (SCR) catalyst for reducing NO_x to N₂ with the reductant, which method comprising fitting the existing exhaust system with at least one NO_x sensor for measuring NO_x in the exhaust gas as the vehicle is driven and correlating a measured NO_x value with a value of at least one measurable parameter indicative of a condition of the engine.
5. A method according to claim 4, comprising the step of using the correlated value to determine the amount of reductant required to reduce the measured value of NO_x by a desired amount for the measured value of the at least one measurable parameter.
6. A method according to claim 5, comprising the step of injecting the amount of reductant so-determined as the vehicle is driven, measuring exhaust gas downstream of the SCR catalyst for the presence of reductant and/or NO_x and adjusting the so-determined amount of reductant to reduce NO_x emissions and/or prevent reductant slip as necessary.

7. A method according to any of claims 1 to 6, wherein the or each correlation step and/or the or each step of determining the amount of reductant is performed by a processor.
- 5 8. A method according to claim 3 or 6, wherein the step of adjusting the so-determined amount of reductant to reduce NO_x emissions and/or prevent reductant slip as necessary is performed by a processor.
- 10 9. A method according to claim 7 or 8, wherein the processor is part of an electronic control unit (ECU).
10. A method according to any preceding claim, wherein the correlated values, the amounts of reductant determined and/or the adjusted reductant amounts are stored as look-up tables or maps.
- 15 11. A method according to claim 10, wherein the correlated values and/or amounts are stored on an ECU.
- 20 12. A method according to claim 8 or 10, wherein the ECU used to perform the or each correlation step, to determine reductant amounts and/or to determine adjusted reductant amounts is replaced with an ECU programmed with look-up tables or maps comprising the determined or adjusted amount of reductant required for any detected value of the at least one measurable parameter.
- 25 13. A method according to claim 1, 2, 3 or any of claims 7 to 12 appendant to claims 1, 2 or 3, wherein at least one NO_x sensor is used to measure the NO_x .
- 30 14. A method according to claim 4, 5 or 6, any of claims 7 to 12 when appendant to claim 4, 5 or 6, and claim 13, wherein the at least one NO_x sensor is removed after the amount of reductant required to reduce the measured value of NO_x for the measured value of the at least one measurable parameter has been determined or the determined value has been adjusted.

15. A method according to any preceding claim, wherein the at least one measurable parameter is exhaust gas temperature.
16. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is mass flow of exhaust gas in the system.
17. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is manifold vacuum.
18. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is ignition timing.
19. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is engine speed.
20. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is throttle position.
21. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is the lambda value of the exhaust gas.
22. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is the quantity of fuel injected in the engine.
23. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is the position of the exhaust gas recirculation (EGR) valve and thereby the amount of EGR.
24. A method according to any of claims 1 to 14, wherein the at least one measurable parameter is boost pressure.
25. A method according to any preceding claim, wherein the reductant is a NO_x specific reactant, such as a nitrogen hydride, e.g. ammonia (NH₃) or hydrazine, or an NH₃ precursor.

26. A method according to claim 25, wherein the NH_3 precursor is urea ($\text{CO}(\text{NH}_2)_2$) or ammonium carbamate ($\text{NH}_2\text{COONH}_4$).

5 27. Apparatus for mapping reductant injection onto NO_x in exhaust gas in a vehicle comprising a lean-burn internal combustion engine and an exhaust system comprising a selective catalytic reduction (SCR) catalyst for reducing NO_x by a desired amount with the reductant, thereby to meet a desired emission standard for NO_x , which apparatus
10 comprising at least one NO_x sensor for measuring NO_x in the exhaust gas, means for measuring at least one measurable parameter indicative of a condition of the engine and means for correlating a measured NO_x value with the value for the at least one measurable parameter.

15 28. Apparatus according to claim 27, comprising means for using the correlated value to determine the amount of reductant required to reduce the measured value of NO_x to N_2 for the measured value of the at least one measurable parameter.

20 29. Apparatus according to claim 28, comprising reductant injection means and means for controlling the injection means to inject the amount of reductant so-determined into the exhaust gas.

25 30. Apparatus according to claim 29, comprising means for measuring exhaust gas downstream of the SCR catalyst for the presence of reductant and NO_x and adjusting the so-determined amount of reductant to reduce NO_x emissions and/or prevent reductant slip as necessary.

30 31. Apparatus according to any of claims 27 to 30, wherein the correlating means, the reductant amount determining means, the injection controlling means and/or the reductant amount adjusting means comprises a processor.

32. Apparatus according to any of claims 27 to 31, comprising means for storing the correlated values, the amounts of reductant determined and/or the adjusted reductant amounts as a look-up tables or maps.

33. Apparatus according to claim 31 or 32, wherein the processor and/or the storing means is part of the electronic control unit (ECU).
34. Apparatus according to any of claims 27 to 33, wherein the at least one NO_x sensor is positioned upstream and/or downstream of the SCR catalyst.
35. Apparatus according to any of claims 27 to 34, comprising means for detecting reductant in exhaust gas downstream of the SCR catalyst.
36. Apparatus according to any of claims 27 to 35, wherein the SCR catalyst comprises copper exchanged zeolite, such as Cu/ZSM5, or platinum e.g. platinum on alumina.
37. Apparatus according to any of claims 27 to 35, wherein the SCR catalyst comprises supported vanadium such as V₂O₅/TiO₂ or a zeolite, such as mordenite.
38. Apparatus according to any of claims 27 to 37, further comprising a source of reductant.
39. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures exhaust gas temperature.
40. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures mass flow of exhaust gas in the system.
41. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures manifold vacuum.
42. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures ignition timing.
43. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures engine speed.

44. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures throttle position.
- 5
45. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures the lambda value of the exhaust gas.
- 10
46. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures the quantity of fuel injected in the engine.
- 15
47. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures the position of the exhaust gas recirculation (EGR) valve and thereby the amount of EGR.
- 20
48. Apparatus according to any of claims 27 to 38, wherein the means for measuring at least one measurable parameter indicative of a condition of the engine measures boost pressure.
- 25
49. A vehicle comprising an apparatus according to any of claims 27 to 48.
50. A vehicle according to claim 49, wherein the engine is a diesel engine, such as a heavy-duty diesel engine.
- 30
51. A method of mapping reductant injection onto NO_x in exhaust gas in a vehicle comprising a lean-burn internal combustion engine and an exhaust system comprising a selective catalytic reduction catalyst for reducing NO_x to N_2 with the reductant, thereby to meet a desired emission standard for NO_x substantially as described herein.
52. A method of retrofitting a vehicle comprising a lean-burn internal combustion engine with a system for meeting a desired emission standard for NO_x , which system comprising means for injecting a reductant into exhaust gas and a selective catalytic reduction catalyst for reducing NO_x to N_2 with the reductant substantially as described herein.

53. Apparatus for mapping reductant injection onto NO_x in exhaust gas in a vehicle comprising a lean-burn internal combustion engine and an exhaust system comprising a selective catalytic reduction catalyst for reducing NO_x to N_2 with the reductant, thereby to meet a
5 desired emission standard for NO_x substantially as described herein.
54. A vehicle comprising an apparatus according to the invention substantially as described herein.